

ROOFING SCHEDULE

Standard thickness 3/16 inch; others available.



Sizes of slate (inches)	No. per square	Exposed when laid 3 inch lap	Approximate nails per square	
			lbs	ozs
24x16	86	10-1/2 in.	1	0
24x14	98	10-1/2 in.	1	2
24x13	106	10-1/2 in.	1	3
24x11	125	10-1/2 in.	1	7
24x12	114	10-1/2 in.	1	5
22x14	108	9-1/2 in.	1	4
22x13	117	9-1/2 in.	1	5
22x12	126	9-1/2 in.	1	7
22x11	138	9-1/2 in.	1	9
22x10	152	9-1/2 in.	1	12
20x14	121	8-1/2 in.	1	6
20x13	132	8-1/2 in.	1	8
20x12	141	8-1/2 in.	1	10
20x11	154	8-1/2 in.	1	12
20x10	170	8-1/2 in.	1	15
20x 9	189	8-1/2 in.	2	3
18x14	137	7-1/2 in.	1	9
18x13	148	7-1/2 in.	1	11
18x12	160	7-1/2 in.	1	13
18x11	175	7-1/2 in.	2	0
18x10	192	7-1/2 in.	2	3
18x 9	213	7-1/2 in.	2	7
16x14	160	6-1/2 in.	1	13
16x12	184	6-1/2 in.	2	2
16x11	201	6-1/2 in.	2	5
16x10	222	6-1/2 in.	2	8
16x 9	246	6-1/2 in.	2	13
16x 8	277	6-1/2 in.	3	2
14x12	218	5-1/2 in.	2	8
14x11	239	5-1/2 in.	2	11
14x10	261	5-1/2 in.	3	3
14x 9	291	5-1/2 in.	3	5
14x 8	327	5-1/2 in.	3	12
14x 7	374	5-1/2 in.	4	4
12x10	320	4-1/2 in.	3	10
12x 9	355	4-1/2 in.	4	1
12x 8	400	4-1/2 in.	4	9
12x 7	457	4-1/2 in.	5	3
12x 6	533	4-1/2 in.	6	1
10x 8	515	3 1/2 in.	5	14
10x 7	588	3 1/2 in.	7	4
10x 6	686	3 1/2 in.	7	13

"exceeding expectations for over 150 years"
www.buckinghamslate.com